

Spring 50


DISTRIBUTED BY **EUROPEAN**
COMPANY




INSTALLATION & MAINTENANCE

- ✓ INSTALLATION GUIDELINES AVAILABLE:
REFER TO STC GUIDE
- ✓ UV STABLE: YES
- ✓ INSTALLATION: NAILS / SEAM TAPE / ADHESIVE
- ✓ INFILL RECOMMENDED

To Order

 888 735 3370

 Europeanco.com

Feel the joy of spring all year round with the Grass Partners (GP) Spring 50 MM artificial grass. The long, 50 mm high deep green blades create an extremely luxurious experience, offering a realistic and vibrant look that mimics the perfect lawn. Enjoy the beauty of a lush, green garden all year long with minimal maintenance.

Specs

Predominant Color: Dark Olive / Field Nut
Origin: Netherlands

Applications

Gardens, Landscape, Infrastructure



Flame
Retardancy



Pet Friendly



Water
Permeable



Softness



UV
Resistance



Made in The
Netherlands

TOTAL WEIGHT:

• 2,155 gr/m2 (± 10%)

TOTAL HEIGHT:

• 52 mm (± 10%)

UV STABILITY:

• DIN 53387 Standard
(6000 Hrs) W.O.M.Test

BACKING:

• SBR Latex coating ± 750 gr/m2

PILE HEIGHT:

• 50 mm (± 10%)

INFILL:

• 5 -10 kg/m2 Silica Sand (0.5 -
1.0 mm round of shape)

CONSTRUCTION:

• Tufted 5/8" Gauge

ROLL LENGTH:

• 25 m1

STITCH RATE:

• 11,340/m2 (± 10%)

ROLL WIDTH:

• 400 cm (±2 cm)

FACE YARN:

• 10,200 Dtex (5.400 Dtex PE
Monofilament, + 4,800 Dtex
PP Texturized)



Wild Romance 65

DISTRIBUTED BY **EUROPEAN**
COMPANY

INSTALLATION & MAINTENANCE

- ✓ INSTALLATION GUIDELINES AVAILABLE:
REFER TO STC GUIDE
- ✓ UV STABLE: YES
- ✓ INSTALLATION: NAILS / SEAM TAPE / ADHESIVE
- ✓ INFILL RECOMMENDED

To Order

 888 735 3370 [Europeanco.com](https://europeanco.com)

Indulge in the ultimate luxury with the Grass Partners (GP) Wild Romance 65 MM artificial grass. Featuring exceptionally long, 65 mm high blades, this turf offers the most elegant look and feel, perfect for creating stunning landscapes and beautiful gardens. Enjoy the lush, dark green tones of Wild Romance all year round with minimal maintenance.

Specs

Predominant Color: Dark Green Olive Green
/ Field Nut

Origin: Netherlands

Applications

Gardens, Landscape, Infrastructure



Flame
Retardancy




Pet Friendly



Water
Permeable



Softness



UV
Resistance



Made in The
Netherlands

TOTAL WEIGHT:

- 120 OZ / SQ FT. (±10%)

TOTAL HEIGHT:

- 2.64 Inch (±10%)

UV STABILITY:

- DIN 53387 Standard
(6000 Hrs) W.O.M.Test

BACKING:

- (SBR) LATEX COMPOUND
± 31 OZ / SQ FT.

PILE HEIGHT:

- 2.56 Inch (±10%)

INFILL:

- ± 22 LB / SQ FT

CONSTRUCTION:

- Tufted 5/8" Gauge

ROLL LENGTH:

- ± 82 Feet

WATER PERMIABILITY:

- ± 16 gallon/ MIN / SQ YD.

STITCH RATE:

- 11,340/m2 (± 10%)

ROLL WIDTH:

- ± 13.12 Feet

FACE YARN:

- 10,200 Dtex (5,400 Dtex PE
Monofilament, + 4,000 Dtex PP
Texturized)

GRASS PARTNERS

Royal Green


DISTRIBUTED BY **EUROPEAN**
COMPANY




INSTALLATION & MAINTENANCE

- ✓ INSTALLATION GUIDELINES AVAILABLE:
REFER TO STC GUIDE
- ✓ UV STABLE: YES
- ✓ INSTALLATION: NAILS / SEAM TAPE / ADHESIVE
- ✓ INFILL RECOMMENDED

To Order

 888 735 3370

 Europeanco.com

Elevate your golfing experience with the Grass Partners (GP) Royal Green 12 MM artificial grass. Designed for professional golf applications, this premium turf features a 12 mm pile height and a stimp rate of 10-11, providing the perfect surface for putting greens. The rich, dark green color adds a touch of elegance and realism, making it an excellent choice for any golfing environment.

Specs

Predominant Color: Emerald Green /
Olive Green
Origin: Netherlands

Applications

Golf Greens



Flame
Retardancy




Pet Friendly



Water
Permeable



Softness



UV
Resistance



Made in The
Netherlands

TOTAL WEIGHT:

- 3.303 gr/m² (± 10%)

BACKING:

- SBR Latex coating ± 988
gram/m²

CONSTRUCTION:

- Tufted 3/16" Gauge

STITCH RATE:

- 63,000/m² (± 10%)

TOTAL HEIGHT:

- 14 mm (± 10%)

PILE HEIGHT:

- 12 mm (± 10%)

ROLL LENGTH:

- 25 m1

ROLL WIDTH:

- 400 cm (±2 cm)

UV STABILITY:

- DIN 53387 Standard
(6000 Hrs) W.O.M.Test

INFILL:

- 5 - 8 kg/m² Silica Sand (0.5 -
1.0 mm round of shape)

FACE YARN:

- PE 9,000/8 Dtex Monofilament
Texturized, 200µm (±5%)



Yellowstone 40

DISTRIBUTED BY **EUROPEAN**
COMPANY

INSTALLATION & MAINTENANCE

- ✓ INSTALLATION GUIDELINES AVAILABLE:
REFER TO STC GUIDE
- ✓ UV STABLE: YES
- ✓ INSTALLATION: NAILS / SEAM TAPE / ADHESIVE
- ✓ INFILL RECOMMENDED

To Order

 888 735 3370 [Europeanco.com](https://europeanco.com)

Grass Partners (GP) Yellowstone 40 MM artificial grass is meticulously crafted to redefine realism in synthetic turf. Designed with precision, this premium artificial grass features non-directional fibers that set new standards of authenticity. The 40 mm pile height replicates the lushness of natural grass, offering an unparalleled underfoot sensation that transforms your landscape into a breathtaking oasis


Specs

Predominant Color: 2-Tone Green

Origin: Netherlands

Applications

Gardens, Landscape, Infrastructure

**Flame
Retardancy****Pet Friendly****Water
Permeable****Softness****UV
Resistance****Made in The
Netherlands****TOTAL WEIGHT:**

- 2.150 gr/m2 (± 10%)

BACKING:

- SBR Latex coating

CONSTRUCTION:

- Tufted 3/8" Gauge

STITCH RATE:

- 11.025/m2 (± 10%)

TOTAL HEIGHT:

- 42 mm (± 10%)

PILE HEIGHT:

- 40 mm (± 10%)

ROLL LENGTH:

- 25 m1

ROLL WIDTH:

- 400 cm (±2 cm)

UV STABILITY:

- DIN 53387 Standard
(6000 Hrs) W.O.M.Test

INFILL:

- 5 - 10 kg/m2 Silica Sand (0.5 -
1.0 mm round of shape)



FACE YARN:

- 12.000 Dtex (4.000/6 Dtex PE
Monofilament (Central spine)
Light texturized 4.700/6 Dtex PE
+ 3.300/8 Dtex PP Texturized)

Midland 40

DISTRIBUTED BY **EUROPEAN**
COMPANY**INSTALLATION & MAINTENANCE**

- ✓ INSTALLATION GUIDELINES AVAILABLE:
REFER TO STC GUIDE
- ✓ UV STABLE: YES
- ✓ INSTALLATION: NAILS / SEAM TAPE / ADHESIVE
- ✓ INFILL RECOMMENDED

To Order 888 735 3370 Europeanco.com

Elevate your outdoor space with the Grass Partners (GP) Midland 40 MM artificial grass, specially crafted for professionals and designed to provide a luxurious, high-end appearance. This wonderfully thick turf is perfect for creating stunning garden projects that exude elegance and sophistication.

Specs

Predominant Color: Pine Olive /
Summer Nut

Origin: Netherlands

Applications

Gardens, Landscape, Infrastructure



Flame
Retardancy




Pet Friendly



Water
Permeable



Softness



UV
Resistance



Made in The
Netherlands

TOTAL WEIGHT:

• 2,865 gr/m2 (± 10%)

TOTAL HEIGHT:

• 42 mm (± 10%)

UV STABILITY:

• DIN 53387 Standard
(6000 Hrs) W.O.M.Test

BACKING:

• SBR Latex coating ± 750 gr/m2

PILE HEIGHT:

• 40 mm (± 10%)

INFILL:

• 5 -10 kg/m2 Silica Sand (0.5 -
1.0 mm round of shape)

CONSTRUCTION:

• Tufted 3/8" Gauge

ROLL LENGTH:

• 25 m1

STITCH RATE:

• 15.750/m2 (± 10%)

ROLL WIDTH:

• 400 cm (±2 cm)

FACE YARN:

• PE 13,800 Dtex (9.000 Dtex PE
Monofilament, C-shape, +4.800 Dtex
PE Texturized)



Denali 30

DISTRIBUTED BY **EUROPEAN**
COMPANY

INSTALLATION & MAINTENANCE

- ✓ INSTALLATION GUIDELINES AVAILABLE:
REFER TO STC GUIDE
- ✓ UV STABLE: YES
- ✓ INSTALLATION: NAILS / SEAM TAPE / ADHESIVE
- ✓ INFILL RECOMMENDED

To Order

 888 735 3370 [Europeanco.com](https://europeanco.com)

Grass Partners (GP) Denali 30 MM artificial grass brings the lush beauty of a real lawn to your space, perfectly blending deep green tones with the vibrant essence of nature. With its sleek 30mm pile height, Denali offers a stunning and realistic appearance, making it ideal for both visual appeal and children's play.


Specs

Predominant Color: 4-Tone Green

Origin: Netherlands

Applications

Gardens, Landscape, Infrastructure

**Flame
Retardancy****Pet Friendly****Water
Permeable****Softness****UV
Resistance****Made in The
Netherlands****TOTAL WEIGHT:**

- ± 64,00 oz

BACKING:

- ± 26.46 oz (SBR) Latex compound

CONSTRUCTION:

- Tufted 3/8" Gauge

STITCH RATE:

- ± 15,750 per sqft

TOTAL HEIGHT:

- 1.34 Inch (±10%)

PILE HEIGHT:

- ± 1.26 inch

ROLL LENGTH:

- ± 99 Feet

ROLL WIDTH:

- ± 13.1 Feet

UV STABILITY:

- DIN 53387 Standard (6000 Hrs) W.O.M.Test

INFILL:

- ± 22 LB / SQ FT

WATER PERMIABILITY:

- > 7 inch/h

FACE YARN:

- 7,600 Dtex/14 ply (60% Dtex PE Monofilament, + 40% Dtex PP Texturized)